

AIR-PAK 75I SCBA

SELF-CONTAINED BREATHING APPARATUS FOR INDUSTRIAL APPLICATIONS



CONTINUOUS INNOVATIONS, CONSISTENT RELIABILITY

INTRODUCING THE AIR-PAK 75i FOR INDUSTRIAL SCBA USERS

With an unmatched record of reliable performance and rugged dependability, Scott Air-Pak SCBAs have earned the confidence and respect of countless Industrial SCBA users. In 2007, our 75th anniversary year, Scott introduced the Air-Pak 75 SCBA to the fire market and is pleased to extend this platform to our Industrial SCBA range. Incorporating the time-tested features you've come to trust from Scott Safety, we've maintained the simple, easy-to-use product you've come to expect and rely on time and time again for dependable respiratory protection.

DEPENDABLE DURABILITY

- Industrial work requiring SCBA protection is intense, physically demanding work. That's why Scott's Air-Pak 75i SCBA is designed with durability, dependability and user focus in mind. Featuring the streamlined backframe of the Air-Pak 75 platform, the Air-Pak 75i SCBA provides a comfortable fit with lower profile for greater freedom of movement to SCBA users in industrial protective clothing during even the most rigorous of on-the-job activities.
- The one-piece backframe is constructed of a lightweight, time-tested, durable aluminum alloy. It is designed to follow the back's contour and places the bulk of the SCBA's weight on the hips, where the fully padded waist belt provides comfortable support to the user. Padded shoulder straps further promote comfort.

QUICK AND RELIABLE DORNING AND DOFFING

- Parachute-Style, oversized harness fasteners designed with gloved hands in mind permit smooth, efficient adjustment for quick donning and doffing. While securely retaining the shoulder straps, the fasteners minimize harness wear and tear, even with frequent use.
- An enhanced latching system with a durable para-aramid fabric band allows for quick and efficient cylinder changes. Simple adjustment of a cam-over center slide permits the installation of 30-, 45-, 60- or 75-minute rated duration cylinders.



EASY TO BREATHE

- The Scott breathing circuit responds rapidly and efficiently to the user's demand for air, making it easier to breathe, especially during periods of peak physical performance. From first-breath activation, Scott offers an SCBA with outstanding breathing performance and exceptional airflow, significantly reducing inhalation and exhalation resistance to minimize user fatigue.

TOP DOWN CONVERTIBILITY

- The Scott Air-Pak 75i SCBA features Scott's unique Top Down Convertibility concept, which allows for a dramatic increase in versatility and compatibility with the entire Scott product line. This design concept enables a user to be trained and fit-tested on a single facepiece to be used for SCBA, air-supplied or air-purifying respiratory protection. Top Down Convertibility simplifies training, minimizes equipment inventories and reduces costs associated with fit-testing multiple facepieces for each employee.

REDUNDANCY OF SAFETY FEATURES

- The Scott Air-Pak 75i SCBA features the Scott E-Z Flo regulator with Vibralert end-of-service indicator. This audible, tactile alarm warns the user of loss of primary pressure by gently vibrating the user's facepiece. This tactile personal alarm minimizes the chance the user's alarm will go unnoticed or be confused with another SCBA user's alarm or outside noise.
- The Scott Air-Pak 75i SCBA features a unique dual-redundant pressure reducer. Unlike all other SCBAs, Scott actually provides two pressure reducers in one, interconnected through an automatic transfer valve. A reduction in primary pressure for whatever reason would trigger an automatic transfer to the secondary circuit. The user is alerted to this transfer by Scott's patented Vibralert alarm, enabling the user to focus attention on safely exiting the hazardous area while providing an uninterrupted supply of air through the secondary circuit.

EASE OF USE

- The E-Z Flo regulator's quick-don mounting system has a 20-year track record of proven performance. A quick quarter turn of the regulator ensures a positive locking mount that prevents it from being accidentally knocked loose. This easy breathing regulator automatically activates the flow of air with the user's first breath. Air entering the facepiece is directed over the lens to prevent fogging.
- An air-saver switch, angled for easy operation with a gloved hand, stops the free flow of air during donning and doffing. This gives the user the advantage of placing the SCBA in a standby mode with an activated cylinder. That means the user can be suited up and ready for action without expending cylinder air.

AIR-PAK 75i SCBA



5500 psi Air-Pak SCBA

5.5: THE LIGHTER, SMALLER CYLINDER FOR YOUR SCBA

Responding to the need for a smaller, lighter SCBA, Scott Safety created the new 5.5 Air-Pak SCBA. By increasing the pressure in the cylinder to 5500 psig, Scott Safety was able to maintain the traditional form, durability and capacity of the standard cylinder while offering over 10% reduction in weight and profile. The 5.5 cylinders are available in 30-minute, 45-minute, 60-minute and 75-minute durations. The 75-minute cylinder, an industry first, is ideal for HAZMAT teams as well as for long-duration cylinder supply to mobile air sources, such as the new 5.5 compatible Scott TRC-1 cart or 5.5 compatible Mobile Air Cart.

SCOTT AIR-PAK 75i SCBA ORDERING INFORMATION

| SCBA Model | Harness | Pressure (psig) | Cylinder | Regulator | EBSS | Airline Options ² | Facepiece | Console | Case | Packaging |
|--------------------|---------------------------|---------------------|----------|----------------------------------------|--------|------------------------------|-------------------------------|---------|-------------|---------------|
| 4 Air-Pak 75i SCBA | 5 Kevlar/Parachute Buckle | 2 2216 | 0 None | 1 E-Z Flo with Vibralert | 0 None | 0 None | 0 None | 1 Gauge | 0 None | 1 One Per Box |
| | | 4 4500 | | 2 E-Z Flo with Vibralert Quick Connect | 2 Dual | 1 Hansen | 1 AV-2000, Kevlar (CS) | | 1 Hard Case | |
| | | 5 2216 with RIC/UAC | | | | 2 Schrader | 2 AV-3000, Kevlar (M) | | 2 Soft Case | |
| | | 7 4500 with RIC/UAC | | | | 4 Hansen HK Plug | 3 AV-3000 Sureseal Kevlar (M) | | | |
| | | 8 5500 | | | | 5 Hansen HK Socket | | | | |
| | | 9 5500 with RIC/UAC | | | | | | | | |

| | | | | | | | | | | | |
|-----|---|---|---|----|---|---|---|---|---|---|---|
| APi | 4 | 5 | X | 00 | X | X | X | X | X | X | X |
|-----|---|---|---|----|---|---|---|---|---|---|---|

Part Number: Select a one or two digit number pre box from the chart above that corresponds to your choice

1 Order cylinders separately
 2 Airline options not available when dual EBSS is installed on Air-Pak 75i SCBA

AIR-PAK 75i SCBA ACCESSORIES



AV-3000 WITH SURESEAL

Fully interchangeable with Scott's full line of SCBA, air-supplied respirators and air-purifying respirators.



EPIC 3 VOICE AMPLIFIER

Streamlined and lightweight, providing robust person-to-person communications with Scott AV-2000, AV-3000 or AV-3000 with SureSeal facepieces.



ALUMINUM/ CARBON CYLINDERS

Scott cylinders are built around DOT specifications with working pressures of 2216, 3000, 4500 or 5500.



BUDDY-BREATHING SYSTEM

A combined Dual EBSS/Airline option affords users mobility while not exposing the recipient or donor to ambient air. Users can also connect to an external air source.



SCOTT PORTABLE AIR SOURCES

The Scott TRC-1 and Scott Mobile Air Cart are portable air sources that can provide an uninterrupted supply of breathing air to up to eight users at a time.

© 2016 Scott Safety. SCOTT, the SCOTT SAFETY Logo, Scott Health and Safety, Air-Pak, Air-Pak Fifty, Air-Pak 75, AV-2000, AV-3000, EPIC, E-Z Flo, EZ-Scape, NxG2, NxG7, Pak-Alert, Pak-Link, Pak Tracker, RIT PAK III, SEMS, Snapchange, Top-Down Convertibility, Vibralert and Visualert are registered and/or unregistered marks of Scott Technologies, Inc. or its affiliates.

Monroe Corporate Center • P.O. Box 569 • Monroe, NC 28111
 Telephone: 800.247.7257 • Facsimile: 704.291.8330
 www.scottsafety.com • sh-sale@tycoint.com

H/S 7013 1/12 ISO 9001 Registered. All rights reserved.

